

ANALYSENZERTIFIKAT
CERTIFICATE OF ANALYSIS

Xylan aus Buchenholz rein	Kat.Nr./Cat.No. :	38500
Xylan from beech wood pure	Lot/Contr.No. :	121187

Parameter parameter	Methode method	Spezifikation specification	Ergebnis result
Summenformel formula		$(C_{10}H_{16}O_9)_n$	
Aussehen appearance		beiges Pulver beige powder	entspricht corresponds
Trocknungsverlust (%) loss on drying	3 h, 110 °C	max. 5.0	4.4
$[\alpha]_D$/ 20 °C	1 % in 5 % NaOH	-75.0° bis/ to -65.0°	-65.4°
Mindesthaltbarkeit minimum shelf life			10/ 2017
Lagerung (°C) storage			+15 bis/ to +30

Die Eignung des Produktes für spezielle Anwendungszwecke wird nicht zugesichert.
Dieses Dokument entbindet nicht von einer branchenüblichen Eingangskontrolle.
We do not guarantee that the product can be used for a special application.
This document does not release you from performing the standard control upon receipt of incoming goods.

SERVA Electrophoresis GmbH
Qualitätskontrolle/ Quality Control

Druckdatum/ printing date: 25.10.2012

Dipl.-Ing. (FH) Bernhard Göckel

Patricia Steinmann

Dieses Dokument ist ein Computerausdruck und deshalb ohne Unterschrift gültig.
This report has been computer generated and does not contain a signature.