



200 Volt High Current Power Supply

HOEFER PS200-HC

- Constant Voltage or Constant Current Mode
- 5-200V, .01-2.00A, 200W
- 4 sets of 4mm Output Jacks
- Ideal Choice for Blotting Applications
- Continuous Runs or 999 Minute Timer
- Certified to EN/UL 61010-1 and CSA 22.2 1010.1 standards

Designed for blotting

The Hoefer PS200-HC is designed for all electrophoretic blot transfer applications. It can be operated in constant current or constant voltage mode.

Convenient and Simple

The small footprint and large handle makes the Hoefer PS200-HC easy to move around and use in your lab.

The large LED is easy to read. Just set the constant parameter, set the timer, if desired, and push Start.

Safety Certified

The Hoefer PS200-HC is designed and certified in accordance with the applicable UL, EN and CSA electrical standards. For safety reasons, we recommend 4mm plugs with fixed insulating sheaths, standard on most Hoefer equipment. There are no adapters required when used with Hoefer equipment!

Ordering Information

Model - PS200-HC



Specifications

- Voltage - 5-200V in 1V steps
- Current - .01-2.00A
- Power - 200W maximum
- Timer - 0-999 minutes
- Output modes - constant voltage or current
- Universal voltage input
- Dimensions - 33.5 x 12.5 x 28 cm
- Weight - 2.4 kg

Safety Certified



300 Volt High Current Power Supply

HOEFER PS300-B

- Constant Voltage or Constant Current Mode
- 10-300V, 4-500 mA, 90W
- 4 sets of 4mm Output Jacks
- Ideal Choice for Most Electrophoresis Techniques
- Continuous Runs or 999 Minute Timer
- Certified to EN/UL 61010-1 and CSA 22.2 1010.1 Standards

Versatile

The Hoefer PS300-B is designed for most electrophoresis techniques. It can be operated in constant current or constant voltage mode. It can be used for submarine gels, mini vertical gels, and semidry transfers.

Convenient and Simple

The small footprint and large handle makes the Hoefer PS300-B easy to move around and use in your lab. The large LED is easy to read. Just set the constant parameter, set the timer, if desired, and push Start.

Safety Certified

The Hoefer PS300-B is designed and certified in accordance with the applicable UL, EN and CSA electrical standards. For safety reasons, we recommend 4mm plugs with fixed insulating sheaths, standard on most Hoefer equipment. No adapters required when used with Hoefer equipment!

Ordering Information

Model - PS300-B



Specifications

Voltage – 10-300V in 1V steps
 Current – 4-500mA
 Power – 90W maximum
 Timer – 0-999 minutes
 Output modes – constant voltage or current
 Universal voltage input
 Dimensions – 33.5 x 12.5 x 28 cm
 Weight – 2.4kg

Safety Certified